

Oil Absorbent Rolls

- Ideal rolls for leaks soaking up and over spray containment happened in large area
- It only absorbs oil-based liquids and hydrocarbons and repels all water
- Absorbing saturation achieved in 15 seconds for oil based liquid
- Unfolded roll fits floor well and can be placed under shelves or machines
- Tear able design for on site application to make cost effective spill containment solution
- Splash white color to catch oil & fuel leakage point after leakage in saturation level
- Available in light, mid and heavy duty
- Absorbent in high fiber construction leave no liquid or fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies



Technical Data Sheet

Brand	UPQUARK
Fluid absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Composition	Melt blown Polypropylene
Color	White
Absorbency Duration	About 15 seconds
Layer	3 layers, SMS
Perforated Pattern cm (inch)	40x25 (16x10") sections
Meets Regulations	29 CFR 1910.22(a)(2), 40 CFR 112.7, 40 CFR 122.26

Optional Product:

Model	Absorbency Level	Sump Capacity(Liter)	Net Weigh(kg)	Sold as	Package
OR3M2850	Light-weight	120	8	1/box	Plastic box
OR3M3850	Mid-weight	180	12	1/box	Plastic box
OR3M4850	Heavy duty-weight	240	16	1/box	Plastic box
OR3M2745	Light-weight	104	7	1/box	Plastic box
OR3M3745	Mid-weight	156	10	1/box	Plastic box
OR3M4745	Heavy duty-weight	207	14	1/box	Plastic box
OR3M2450	Light-weight	60	4	1/box	Plastic box
OR3M3450	Mid-weight	90	6	1/box	Plastic box
OR3M4450	Heavy duty-weight	120	8	1/box	Plastic box

Note:

1. Cannot be used together with oil stain cleaning products such as degreasing agents.
2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.