

UP-1506 (6 Drum Spill Pallet)

- Linear low density polyethylene (LLDPE) construction resists UV rays, rust, corrosion and most chemicals
- Ideal for 6 ea 55 gallon drums' storage & spill containment
- Sump capacity up to 1100 liters
- In compliance with EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
- 2 ea gratings for contained liquid level monitoring
- 50cm height for easy step up without ladder
- Optional for drain plug selection
- 2 ways pockets are compatible with most forklift trucks



Technical Data Sheet

Brand	UPQUARK
Model	UP-1506
Included	1 pc Spill Pallet Base with 2 pcs Gratings
Dimensions LxWxH cm (in.)	220 x 130 x 50 (86x51x19")
Color	Yellow/ Black
Material	Linear low density polyethylene (LLDPE)
Weight kg(lb)	102 (225)
Sump Capacity liters (gal)	1,100 (290)
Recommend load capacity (UDL) kg (lb)	3,800 (8,377)
Forklift Channels cm (in.)	Width 23 (9"), Inside Spread 19 (7.5"), Height 14 (5.5")
Regulation Standard	PA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26, Oil storage regulation 2001,PPG26
Style	Drum Spill Containment Pallets
Liquid Discharge Solution	Automatic Discharge Pump (UP-1999) or Plug Drain

