

Universal Absorbent Pads

- It soaks up oil, coolants, solvents and water-based fluids anywhere in your facility
- Catch up spill liquid in short time to avoid pollution spray
- Plastic packaging will not be ruined by water and self-extinguish with fire
- Tear able design for on- site application to make cost effective spill containment solution
- Neat and dense dimple on absorbent surface enhance product strength
- Available in light, mid and heavy duty
- Absorbent in high fiber construction leave no fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies



Technical Data Sheet

Brand	UPQUARK
Fluid absorbed	Most industrial liquids
Dimensions cm (inch)	40x 50 (16x20")
Composition	Melt blown Polypropylene
Color	Gray
Absorbency Duration	About 15 seconds
Layer	3 layers, SMS
Perforated Pattern cm (inch)	40x25 (16x10") sections
Meets Regulations	29 CFR 1910.22(a)(2)

Optional Product:

Model	Absorbency Level	Sump Capacity(Liter)	Net Weigh(kg)	Sold as	Package
UP3M220	Light-weight	120	8	200/box	Plastic box
UP3M310	Mid-weight	90	6	100/box	Plastic box
UP3M410	Heavy duty-weight	120	8	200/box	Plastic box
UP3M220D	Light-weight	120	8	200/box	Dispenser box
UP3M310D	Mid-weight	90	6	100/box	Dispenser box
UP3M410D	Heavy duty-weight	120	8	200/box	Dispenser box

Note:

1. Not recommended to use for toxic, harmful, corrosive liquids unless this product is the only one in hand when a chemical liquid leaks. Please refer to the article for specific reasons.
2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.